

Mosaic™ Programme mechanisms

multi-support single and multiple sockets: German standard



Selection chart for boxes, supports and plates **p. 838-839**

| Pack | Cat.Nos | Multi-support single sockets - German standard |
|------|-----------------------|--|
| | | For installation in flush-mounting box, surface-mounting box, floor box, column module, desktop multi-outlet extension, office module and trunking 2 modules |
| 10 | 0 772 11 ¹ | 2P+E with shutters for child protection ○ White - automatic terminals |
| 10 | 0 772 13 ¹ | ○ White - with special tap-off screw and 4 mm ² screw terminals |
| 10 | 0 772 18 ¹ | ● Red - automatic terminals |
| 10 | 0 792 13 ¹ | ● Alu - screw terminals |
| 10 | 0 787 02 ¹ | ○ White antimicrobial - screw terminals |
| 10 | 0 772 16 ¹ | ● Green antimicrobial - automatic terminals |
| 10 | 0 772 17 ¹ | ● Orange antimicrobial - automatic terminals |
| 10 | 0 772 20 ¹ | ● Red antimicrobial - screw terminals |
| 10 | 0 772 10 ¹ | 2P+E without child protection ○ White - screw terminals |
| 10 | 0 772 45 ¹ | 2P+E angled 45° ○ White - automatic terminals |
| 10 | 0 772 14 ¹ | 2P+E tamperproof ● Red - screw terminals To be used with the tamperproof insert Cat.No 0 502 99 |
| 1 | 0 772 31 | 2P+E "Access Design" Special for disabled persons Simple action on the lever allows easy plug-in or unplug ○ White antimicrobial |
| 10 | 0 772 19 | 2P+E with cover ○ White antimicrobial - automatic terminals |
| 10 | 0 772 12 | 2P+E with indicator ○ White antimicrobial - automatic terminals Indicator 230 V - 2.4 mA supplied |

| Pack | Cat.Nos | Multi-support multiple sockets - German standard |
|------|----------------------|--|
| | | For installation in flush-mounting box, surface-mounting box, floor box, column module, desktop multi-outlet extension and office module Inclined 45° - IK 07 Connection by automatic terminals |
| 10 | 0 772 52 | 2 x 2P+E ○ White |
| 10 | 0 772 90 | ○ White - with indicator 230 V - 2.4 mA (supplied) |
| 10 | 0 792 82 | ● Alu |
| 10 | 0 772 72 | ● Red |
| 10 | 0 772 91 | ● Red - with indicator 230 V - 2.4 mA (supplied) |
| 10 | 0 772 81 | ● Red - tamperproof. To be used with tamperproof insert Cat.No 0 502 99 |
| 10 | 0 772 92 | ● Red - tamperproof, with indicator 230 V - 2.4 mA (supplied). To be used with tamperproof insert Cat.No 0 502 99 |
| 10 | 0 772 53 | 3 x 2P+E ○ White |
| 10 | 0 792 83 | ● Alu |
| 10 | 0 772 82 | ● Red |
| 10 | 0 772 73 | ● Red - tamperproof. To be used with tamperproof insert Cat.No 0 502 99 |
| 5 | 0 772 54 | 4 x 2P+E ○ White |
| 5 | 0 772 83 | ● Red |
| 5 | 0 772 74 | ● Red - tamperproof. To be used with tamperproof insert Cat.No 0 502 99 |
| 10 | 0 502 99 | Tamperproof insert Tamperproof insert for socket Fits directly into the plug |
| 10 | N 0 676 63 | Green light for socket outlets 230 V Consumption 2.4 mA To be wired |

1: Can be installed in receptacles for floor sockets (p. 389)

