


Cable ties, made in PA66, Halogen Free. Available in 13 sizes, from 2.4x75 to 9x914mm. To complete the series are available also: heavy duty wiring ties, re-openable cable ties, cable ties with eyelet and cable ties with plate.

Colour	Colourless	Dimensions LxH (mm)	3.6x203
Material	Polyamide 66	Tensile stress (daN)	18
Terminal grip capacity Ø	2.5 - 55.0 mm	Glow Wire Test	650 °C
Type	Standard	Type of material	Halogen-free in compliance with EN 50267-2-2
Electrocod	3640	Standard	EN 62775
Fume corrosiveness	< 5%	Flame resistance in compliance with UL 94	V2
Oxygen limit index	27%	Installation temperature	-5 +60 °C
Service temperature range	-40 °C +80 °C (max.peaks 135 °C)		


BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Ethyl alcohol		
Resistant	Limited resistance	Limited resistance	Limited resistance	Resistant	Resistant	Resistant	Resistant	Resistant	Resistant	Resistant

DIMENSIONAL



TECHNICAL SYMBOLOGY



STANDARDS/APPROVALS

